

LITHIUM BATTERIES



**ER20505M
3.6V 3800mAh**

lithium-thionyl chloride batteries

Electrical characteristics

(Stored for one year or less)

◉ Nominal Capacity (4 mA to 2.0V, at 25°C)	3800 mAh
◉ Nominal voltage	3.6V
◉ Max continuous discharge current	600 mA
◉ Max. Pulse current Current value is obtaining 2.0V cell voltage when pulse is applied for 15 seconds at 50% discharge depth at 25°C	1500mA
◉ Storage temperature	20°C ~ 30°C
◉ Operating temperature	-55°C ~ 85°C
◉ Weight(approx)	35g

WARNING:

Fire, explosion and severe burn hazard. Do not recharge, crush, disassemble, heat above 100°C, incinerate or expose contents to water.

Key features

- High and stable operating voltage
- Low self-discharge rate
Less than 1% after 1 year of storage at 20°C
- Stainless steel container
- Hermetic glass-to-metal sealing
- Non-flammable electrolyte
- Compliant with IEC 86-4 safety standard
- Non-restricted for transport


Main applications

- TPMS
- Alarms and security system
- Memory back-up
- Tracking system
- Automotive electronics
- Professional electronics
- Computer real-time clocks


.....

LITHIUM BATTERIES


Typical discharge at 25°C



Voltage plateau versus Current and Temperature




Capacity versus Current and Temperature



ER20505M

lithium-thionyl chloride batteries



Unit: mm

Available Terminations

-/P	Axial Pin
-/T /PT2	Radial Pin
-/PT /TP	Polarized Tab